

MODEL		AC-09TK-T	AC-12TK-T	AC-12TK-T WIFI
Capacitate		9000BTU	12000BTU	12000BTU WI-FI
Tip		Pompa de incalzire	Pompa de incalzire	Pompa de incalzire
Tip de control		telecomanda	telecomanda	telecomanda
Capacitate de racire declarata	W	2600(1000~3100)	3500(1050~3700)	3500(1050~3700)
Capacitate de incalzire declarata	W	2600(1000~3800)	3500(1050~4500)	3500(1050~4500)
Pdesignc	W	2600	3500	3500
Pdesignh	W	2600	3500	3500
SEER declarat	W/W	6.6	6.6	6.6
SCOP declarat	W/W	4.0	4.0	4.0
Clasa Energetica racire		A+	A+	A+
Clasa Energetica incalzire		A++	A++	A++
Consum anual de energie kwh/a	Racire	138	186	186
	Incalzire	910	1225	1225
Indepartare umezeala litri/h		0,8	1	1
Putere sunet in interior dB(A)	High	50	50	50
	Med	46	46	46
	Low	38	38	38
Putere sunet in exterior dB(A)		60	62	62
Alimentare curent		220-240V~/50HZ/1P	220-240V~/50HZ/1P	220-240V~/50HZ/1P
Interval voltaj V		165-265	165-265	165-265
Curent de operare	Racire A	3.6(1.3-5.0)	4.9(1.3~6.1)	4.9(1.3~6.1)
	Incalzire A	3.2(1.3-6.4)	4.3(1.3~7.8)	4.3(1.3~7.8)
Consum de energie	Racire W	800(290~1100)	1080(290~1330)	1080(290~1330)
	Incalzire W	700(290~1400)	940(290~1700)	940(290~1700)
Refrigerent G		R410A/0.80kg	R410A/1.00kg	R410A/1.00kg
Compresor	Tip	Rotativ	Rotativ	Rotativ
	Model	43A23EEL&PIKD	43A26DEL-PJKE	43A26DEL-PJKE
	MFG	RECHI	RECHI	RECHI
Circulare aer in interior racire/incalzire m³/h		650/650	650/650	650/650
Tip ventilator de interior		Cross Flow	Cross Flow	Cross Flow
Model ventilator de interior		21090042I(AC)	21090042I(AC)	21090042I(AC)
Viteza ventilator de interior H/M/L	Racire RPM	900/850/800	900/850/800	900/850/800
	Incalzire RPM	950/850/800	950/850/800	950/850/800
	Uscare RPM	800	800	800
	Sleep RPM	800	800	800
Ventilator de interior output motor W		20	20	20
Tip ventilator de exterior		Propeller	Propeller	Propeller
Model ventilator de exterior		GZSDJ-29(DC)	GZSDJ-29(DC)	GZSDJ-29(DC)
Viteza ventilator de exterior RPM		860/700/500	860/700/500	860/700/500
Ventilator de exterior output motor W		33	33	33
Cabluri de conectare		4×1.0mm²	4×1.5mm²	4×1.5mm²
Dispozitiv de expansiune		Valva electronica de expansiune	Valva electronica de expansiune	Valva electronica de expansiune
Tevi de conectare (inch)	Gaz	3/8"	3/8"	3/8"
	Lichid	1/4"	1/4"	1/4"
Dimensiune neta (mm)	Interior	800×280×185	800×280×185	800×280×185
	Exterior	760×552×256	700×552×256	760×552×256
Greutate neta (kg)	Interior	10	10	10
	Exterior	30	30	32
Dimensiuni ambalaj (mm)		885×366×278 (interior) 863×600×325 (exterior)	885×366×278 (interior) 863×600×325 (exterior)	885×366×278 (interior) 863×600×325 (exterior)
Greutate bruta (kg)	Interior	12	12	12
	Exterior	33 (fara tevi) 34 (cu tevi)	36 (fara tevi) 37 (cu tevi)	36 (fara tevi) 37 (cu tevi)
Capacitate incarcare (fara tevi)	20'/40'GQ /40'HQ	109/222/260	109/222/260	109/222/260

